

```

└─/run/user/0          tmpfs          tmpfs          rw,nosuid,nodev,relatime,size=1628820k,nr_inodes=407205,mode=700,inode shared
root@Devel64-1: /git/ipfire-2.x # unshare --cgroup
root@Devel64-1: /git/ipfire-2.x # unshare --mount
root@Devel64-1: /git/ipfire-2.x # unshare --propagation=slave
root@Devel64-1: /git/ipfire-2.x # unshare --pid --fork
root@Devel64-1: /git/ipfire-2.x # unshare --time
root@Devel64-1: /git/ipfire-2.x # unshare --uts
root@Devel64-1: /git/ipfire-2.x # unshare --mount-proc=${BUILD_DIR}/proc
root@Devel64-1: /git/ipfire-2.x # unshare --kill-child
root@Devel64-1: /git/ipfire-2.x # findmnt -o+PROPAGATION
TARGET          SOURCE          FSTYPE          OPTIONS          PROPAGATION
/
└─/dev
  └─/dev/pts      devtmpfs        devtmpfs        rw,nosuid,relatime,size=8120860k,nr_inodes=2030215,mode=755,inode64 private
  └─/dev/shm      tmpfs           tmpfs           rw,nosuid,nodev,inode64 private
  └─/dev/mqueue  mqueue         mqueue         rw,nosuid,nodev,noexec,relatime private
  └─/dev/hugepages hugetlbfs      hugetlbfs      rw,relatime,pagesize=2M private
└─/run
  └─/run/lock    tmpfs          tmpfs          rw,nosuid,nodev,noexec,relatime,size=5120k,inode64 private
  └─/run/credentials/systemd-sysusers.service
  └─/run/user/0  ramfs         ramfs         ro,nosuid,nodev,noexec,relatime,mode=700 private
└─/sys
  └─/sys/kernel/security securityfs     securityfs     rw,nosuid,nodev,noexec,relatime private
  └─/sys/fs/cgroup cgroup2[../../../../] cgroup2       rw,nosuid,nodev,noexec,relatime,nsdelegate,memory_recursiveprot private
  └─/sys/fs/pstore pstore       pstore       rw,nosuid,nodev,noexec,relatime private
  └─/sys/fs/bpf   bpf         bpf         rw,nosuid,nodev,noexec,relatime,mode=700 private
  └─/sys/kernel/debug debugfs      debugfs      rw,nosuid,nodev,noexec,relatime private
  └─/sys/kernel/tracing tracefs     tracefs     rw,nosuid,nodev,noexec,relatime private
  └─/sys/fs/fuse/connections fusectl     fusectl     rw,nosuid,nodev,noexec,relatime private
  └─/sys/kernel/config configfs    configfs    rw,nosuid,nodev,noexec,relatime private
└─/proc
  └─/proc/sys/fs/binfmt_misc systemd-1    autofs      rw,relatime,fd=29,pgrp=0,timeout=0,minproto=5,maxproto=5,direct,pipe_i private
    └─/proc/sys/fs/binfmt_misc binfmt_misc binfmt_misc rw,nosuid,nodev,noexec,relatime private
  └─/proc        proc        proc        rw,nosuid,nodev,noexec,relatime private
root@Devel64-1: /git/ipfire-2.x # █

```